

**SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product code : Ravvilux  
Trades code : A70-025  
Product line: Tintolav

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

For levelling and refreshing tissues

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

**1.3. Details of the supplier of the safety data sheet**

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: [info@tintolav.com](mailto:info@tintolav.com) - Sito internet: [www.tintolav.com](http://www.tintolav.com)

Email tecnico competente: [a.conedera@tintolav.com](mailto:a.conedera@tintolav.com)

National contact: Malta: Emergency Ambulance 112  
Accident & Emergency Department 2545 4030

**1.4. Emergency telephone number**

The UK National Poisons Emergency number +44 (0)870 600 6266  
London: Emergency 24 hour telephone +44 (0) 207188 0100

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS02, GHS07, GHS09

Hazard Class and Category Code(s):

Flam. Aerosol 1, Skin Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 2

Hazard statement Code(s):

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Aerosol that ignites easily even at low temperatures, fire risk

If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

The product, if brought into contact with skin can cause skin sensitization.

Warning: Vapours inhalation may cause sleepiness and giddiness

The product is dangerous to the environment as it is toxic to aquatic life with long lasting effects

The repeated inhalation of vapors can cause drowsiness and giddiness.  
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.  
The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

## 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):  
GHS02, GHS07, GHS09 - Danger



Hazard statement Code(s):  
H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.

Supplemental Hazard statement Code(s):  
not applicable

Precautionary statements:

Prevention

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Do not pierce or burn, even after use.
- P261 - Avoid breathing spray.
- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.

Response

- P302+P352 - IF ON SKIN: Wash with plenty of water water and soap.
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

Storage

- P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

Disposal

- P501 - Dispose of contents / container in accordance with local and national regulations.

Contains:

Isobutane, Butane, Propane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, White mineral oil (petroleum), Eucalyptus globulus oil, turpentine, oil, dipentene

Content of VOC ready to use condition: 89,52 %

## 2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

## SECTION 3. Composition/information on ingredients

### 3.1 Substances

Irrilevant

**3.2 Mixtures**

Refer to paragraph 16 for full text of hazard statements

| Substance                                       | Concentration | Classification   | Index        | CAS       | EINECS    | REACH                     |
|---|---------------|--|--------------|-----------|-----------|---------------------------|
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic | > 30 <= 50%   | Flam. Liq. 2, H225;<br>Asp. Tox. 1, H304;<br>Skin Irrit. 2, H315;<br>STOT SE 3, H336;<br>Aquatic Chronic 2, H411 |              |           | 927-510-4 | 01-2119475<br>515-33-xxxx |
| Butane  | > 20 <= 30%   | Flam. Gas 1, H220  | 601-004-00-0 | 106-97-8  | 203-448-7 |                           |
| Isobutane                                       | > 10 <= 20%   | Flam. Gas 1, H220  | 601-004-00-0 | 75-28-5   | 200-857-2 |                           |
| Propane   | > 10 <= 20%   | Flam. Gas 1, H220;<br>Press. Gas, H280   | 601-003-00-5 | 74-98-6   | 200-827-9 |                           |
| White mineral oil (petroleum)                   | > 5 <= 10%    | Asp. Tox. 1, H304  |              | 8042-47-5 | 232-455-8 |                           |

**SECTION 4. First aid measures****4.1. Description of first aid measures**

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with water and soap.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water for at least 10 minutes.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

If skin irritation occurs: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

**SECTION 5. Firefighting measures****5.1. Extinguishing media**

Advised extinguishing agents:

CO2 or dry powder extinguisher

Extinguishing means to avoid:

Direct jets of water

## **5.2. Special hazards arising from the substance or mixture**

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance ( protect the head using a safety helmet).

## **5.3. Advice for firefighters**

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

## **SECTION 6. Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear gloves and protective clothing

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing Suitable: LaTeX, nitrile, PVC

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

### **6.2. Environmental precautions**

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

### **6.3. Methods and material for containment and cleaning up**

6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

### **6.4. Reference to other sections**

Refer to paragraphs 8 and 13 for more information

## **SECTION 7. Handling and storage**

**7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors

Use extreme caution when handling the product. Avoid shock or friction.

In residential areas do not use on large surfaces.

Do not smoke at work

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

See also paragraph 8 below.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

**7.3. Specific end use(s)**

Industrial Manufacturing:

Handle with extreme caution.

Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):

Handle with care.

Store in ventilated place away from heat sources,

Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Related to contained substances:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic:

Derived No Effect Levels (DNELS)

Long-term effects-Oral-systemic-> Work n/a-General population 149 mg/kg bw/day

Long-term systemic effects-Dermal--> Work 300 mg/kg bw/day-General population 149 mg/kg bw/day

Long-term systemic effects – Inhalation--Work 2085 > mg/m-General population 447 mg/m

Butane:

TLV (ACGIH) = 1000 ppm

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1900 mg/m 10 hour (s).

TWA: 800 ppm 10 hour (s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1900 mg/m 8 hour (s).

TWA: 800 ppm 8 hour (s).

Butane EH40 WEL TWA 600 ppm 1.450 mg/m<sup>3</sup>

**Isobutane:**

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1900 mg/m 10 hour (s).

TWA: 800 ppm 10 hour (s)

**Propane:**

TLV: (Aliphatic hydrocarbon gases) 1000 ppm as TWA; (ACGIH 2005).

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1800 mg/m 10 hour (s).

TWA: 1000 ppm 10 hour (s).

OSHA PEL (United States, 6/2010).

TWA: 1800 mg/m 8 hour (s).

TWA: 1000 ppm 8 hour (s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1800 mg/m 8 hour (s).

TWA: 1000 ppm 8 hour (s)

**White mineral oil (petroleum):**White Mineral Oil ACGIH TLV STEL 10 mg/m<sup>3</sup>

- Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

DNEL

Systemic effects Long term Consumers inhalation = 2085 (mg/m<sup>3</sup>)

Systemic effects Long term Consumers dermal = 300 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 149 (mg/kg bw/day)

**8.2. Exposure controls****Appropriate engineering controls:**

Industrial Manufacturing:

No specific monitoring foreseen

**Private households (= general public = consumers):**

No specific checks planned

**Public domain (administration, education, entertainment, services, craftsmen):**

No specific monitoring foreseen

**Individual protection measures:**

(a) Eye / face protection

Wear mask

(b) Skin protection

(i) Hand protection

Manipulate with gloves. The gloves should be checked before being used. Use a technique suitable for the removal of gloves (without touching the outside of the glove) to avoid skin contact with this product dispose of contaminated gloves after use in accordance with the legislation and good laboratory practices. Wash and dry your hands.

Selected protective gloves shall comply with the requirements of EU Directive 89/686/EEC and

EN 374 standards arising therefrom.

Full contact

Material: nitrile rubber

minimum thickness: 0.11 mm

permeation time: 480 min

(ii) Other

Avoid direct contact with the skin

Better is to use cotton antistatic clothing

(c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

| Physical and chemical properties             | Value                           | Determination method |
|--|---------------------------------|----------------------|
| Appearance                                   | Colorless liquid under pressure |                      |
| Odour  | characteristic-white musk       |                      |
| Odour threshold                              | not determined                  |                      |
| pH   | irrelevant                      |                      |
| Melting point/freezing point                 | < -100 °C (liquid gas)          |                      |
| Initial boiling point and boiling range      | > -42 °C (liquid gas)           |                      |
| Flash point                                  | < -80 °C (liquid gas)           | ASTM D92             |
| Evaporation rate                             | irrelevant                      |                      |
| Flammability (solid, gas)                    | inflammabile                    |                      |
| Upper/lower flammability or explosive limits | 9,5% vol / 1,8% vol             |                      |
| Vapour pressure                              | 3,2 bar                         |                      |
| Vapour density                               | > 2 (liquid gas)                |                      |
| Relative density                             | 0,65 kg/l                       |                      |
| Solubility                                   | liposoluble                     |                      |
| Water solubility                             | not determined                  |                      |
| Partition coefficient: n-octanol/water       | not determined                  |                      |
| Auto-ignition temperature                    | > 400 °C                        |                      |
| Decomposition temperature                    | not determined                  |                      |
| Viscosity                                    | not determined                  |                      |
| Explosive properties                         | not explosive                   |                      |
| Oxidising properties                         | non-oxidizing                   |                      |
| Container volume                             | 800 ml                          |                      |
| Product volume                               | 600 ml                          |                      |
| Pressure to 20°C                             | 3,2 bar                         |                      |
| Deformation pressure                         | 16,5 bar                        |                      |
| Burst pressure of the container              | 18 bar                          |                      |

| Physical and chemical properties | Value   | Determination method |
|----------------------------------|---------|----------------------|
| Flash point of liquid phase      | < 21 °C |                      |
| Propellant inflammability        | < 0 °C  |                      |

**9.2. Other information**

Content of VOC ready to use condition: 89,52 %

**SECTION 10. Stability and reactivity****10.1. Reactivity**

No reactivity hazards

**10.2. Chemical stability**

No hazardous reaction when handled and stored according to provisions.

**10.3. Possibility of hazardous reactions**

There are no hazardous reactions

**10.4. Conditions to avoid**

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 ° C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

**10.5. Incompatible materials**

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

**10.6. Hazardous decomposition products**

Does not decompose when used for intended uses.

**SECTION 11. Toxicological information****11.1. Information on toxicological effects**

ATE(mix) oral = ∞

ATE(mix) dermal = ∞

ATE(mix) inhal = 10.869,6 mg/l/4 h

(a) acute toxicity: based on available data, the classification criteria are not met.



(b) skin corrosion/irritation: If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

White mineral oil (petroleum): Skin: repeated or prolonged Contact may cause irritation and dermatitis

(c) serious eye damage/irritation: White mineral oil (petroleum): Eyes: Irritating

(d) respiratory or skin sensitization: The product, if brought into contact with skin can cause skin sensitization.

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: based on available data, the classification criteria are not met.

(h) specific target organ toxicity (STOT) single exposure: Warning: Vapours inhalation may cause sleepiness and giddiness

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic: Specific target organ toxicity (single exposure):  
STOT Single Exp. 3 (hazard statement: H336 May cause drowsiness or dizziness. Affected organs: Nervous system. Route of exposure: Inhalation

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic:

LD50 Oral, Rat LD50 > 5840 mg/kg bw (rat)

LC50, Inhalation (4 h) Rat > 23.3 mg/L air (male/female)

LD50, Dermal Rat > = 2800 mg/Kg bw

LD50 (rat) Oral (mg/kg body weight) = 5840

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2800

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 23,3

Butane:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658

Isobutane:

LD50 (rat) Oral (mg/kg body weight) = 570000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 570000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658000

Propane:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 410000

White mineral oil (petroleum):

TOXICOLOGICAL DATA: Meaningful toxicological test data could not be found for this product.

Carcinogenicity Data: The ingredient(s) of this product is (are) not classed as carcinogenic by ACGIH, IARC, OSHA or NTP.

Reproductive Data: No adverse reproductive effects are anticipated.

Mutagenicity Data: No adverse mutagenic effects are anticipated.

Teratogenicity Data: No adverse teratogenic effects are anticipated.

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 4,5

## SECTION 12. Ecological information

---

### **12.1. Toxicity**

Related to contained substances:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic:

LC50 (83d): > 13.4 mg/l/83d *Oncorhynchus mykiss* (rainbow trout)

IC50 (72 h): > 10 mg/l/72 h *Pseudokirchnerella subcapitata*

EC50 (48 h): 12 mg/l/48 h *Daphnia magna*

C(E)L50 (mg/l) = 10

Butane:

C(E)L50 (mg/l) = 7,71

Isobutane:

C(E)L50 (mg/l) = 7,71

Propane:

C(E)L50 (mg/l) = 7,71

White mineral oil (petroleum):

Ecotoxicity: Not available. Low acute toxicity to aquatic organisms.

Environmental Fate: Not available. Can be dangerous if allowed to enter drinking water intakes. Do not contaminate domestic or irrigation water supplies, lakes, streams, ponds, or rivers. This product is biodegradable.

C(E)L50 (mg/l) = 100

The product is dangerous for the environment as it is toxic to aquatic organisms following acute exposure.

Use according to good working practices to avoid pollution into the environment.

### **12.2. Persistence and degradability**

Related to contained substances:

White mineral oil (petroleum):

Biotic degradation: degradable

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

### **12.6. Other adverse effects**

No adverse effects

---

## **SECTION 13. Disposal considerations**

**13.1. Waste treatment methods**

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

**SECTION 14. Transport information****14.1. UN number**

ADR/RID/IMDG/ICAO-IATA: 1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

**14.2. UN proper shipping name**

ADR/RID/IMDG: AEROSOL infiammabili

ADR/RID/IMDG: AEROSOL flammable

ICAO-IATA: AEROSOL flammable

**14.3. Transport hazard class(es)**

ADR/RID/IMDG/ICAO-IATA: Class : 2

ADR/RID/IMDG/ICAO-IATA: Label : Limited quantities

ADR: Tunnel restriction code : D

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS : F-D, S-U

**14.4. Packing group**

ADR/RID/IMDG/ICAO-IATA: --

**14.5. Environmental hazards**

ADR/RID/ICAO-IATA: Product is environmentally hazardous

IMDG: Marine polluting agent : Yes

**14.6. Special precautions for user**

No data available.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

It is not intended to carry bulk

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso category:

P3a - FLAMMABLE AEROSOLS

E2 - ENVIRONMENTAL HAZARDS

---

REGULATION (EU) No 1357/2014 - waste:

HP3 - Flammable

HP4 - Irritant — skin irritation and eye damage

HP5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

### **15.2. Chemical safety assessment**

The supplier has made an assessment of chemical safety

## **SECTION 16. Other information**

### **16.1. Other information**

Description of the hazard statements exposed to point 3

H225 = Highly flammable liquid and vapour.

H304 = May be fatal if swallowed and enters airways.

H315 = Causes skin irritation.

H336 = May cause drowsiness or dizziness.

H411 = Toxic to aquatic life with long lasting effects.

H220 = Extremely flammable gas.

H280 = Contains gas under pressure; may explode if heated.

Classification based on data of all mixture components

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

\*\* The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.

---